

Dymonic 100

Table of Contents




Dymonic 100 Color Chart - EN	1
Dymonic 100 Almond SDS - EN	3
Dymonic 100 Almond SDS (CAN) - EN	23
Dymonic 100 Aluminum Stone SDS - EN	43
Dymonic 100 Aluminum Stone SDS (CAN) - EN	69
Dymonic 100 Anodized Aluminum SDS - EN	95
Dymonic 100 Anodized Aluminum SDS (CAN) - EN	115
Dymonic 100 Beige SDS - EN	135
Dymonic 100 Beige SDS (CAN) - EN	155
Dymonic 100 Black SDS - EN	175
Dymonic 100 Black SDS (CAN) - EN	201
Dymonic 100 Bronze SDS - EN	227
Dymonic 100 Bronze SDS (CAN) - EN	247
Dymonic 100 Buff SDS - EN	267
Dymonic 100 Buff SDS (CAN) - EN	287
Dymonic 100 Dark Bronze SDS - EN	307
Dymonic 100 Dark Bronze SDS (CAN) - EN	327
Dymonic 100 Gray SDS - EN	347
Dymonic 100 Gray SDS (CAN) - EN	367
Dymonic 100 Gray Stone SDS - EN	387
Dymonic 100 Gray Stone SDS (CAN) - EN	407
Dymonic 100 Harford Green SDS - EN	427
Dymonic 100 Harford Green SDS (CAN) - EN	445
Dymonic 100 Ivory SDS - EN	463
Dymonic 100 Ivory SDS (CAN) - EN	485
Dymonic 100 Light Bronze SDS - EN	507
Dymonic 100 Light Bronze SDS (CAN) - EN	525
Dymonic 100 Limestone SDS - EN	543
Dymonic 100 Limestone SDS (CAN) - EN	571
Dymonic 100 Natural Clay SDS - EN	599

Dymonic 100 Natural Clay SDS (CAN) - EN	619
Dymonic 100 Off White SDS - EN	639
Dymonic 100 Off White SDS (CAN) - EN	659
Dymonic 100 Precast White SDS - EN	679
Dymonic 100 Precast White SDS (CAN) - EN	699
Dymonic 100 Redwood Tan SDS - EN	719
Dymonic 100 Redwood Tan SDS (CAN) - EN	741
Dymonic 100 Sandalwood SDS - EN	763
Dymonic 100 Sandalwood SDS (CAN) - EN	783
Dymonic 100 Stone SDS - EN	803
Dymonic 100 Stone SDS (CAN) - EN	823
Dymonic 100 White SDS - EN	843
Dymonic 100 White SDS (CAN) - EN	871

Dymonic® 100

Standard Colors

Colors shown are approximate and may not reflect the shade precisely. Different lighting conditions can influence color appearance, for truer color please view in daylight. Colors are not stocked in all available package types. Minimum order quantities will apply for custom colors and alternative packaging. For more information, please contact Tremco Customer Service.

	PRECAST WHITE
	ANODIZED ALUMINUM
	IVORY
	OFF WHITE
	ALMOND
	STONE
	GRAY STONE
	LIMESTONE
	GRAY
	NATURAL CLAY
	BUFF
	ALUMINUM STONE
	SANDALWOOD
	BEIGE
	LIGHT BRONZE
	REDWOOD TAN
	HARTFORD GREEN
	BRONZE
	DARK BRONZE
	BLACK
	WHITE

TREMCO®

Dymonic® 100

Dymonic® 100

High Performance, High Movement, Single-Component, Polyurethane Sealant

Dymonic® 100 is a medium modulus, low VOC, UV stable, non-sag polyurethane sealant.

Applicable Standards

ASTM C 920 Type S, Grade NS, Class 50, Use NT, T, M, A, O, I;
CAN/CGSB-19.13-M87; U.S. Federal Specification TT-S-00230C,
Class A, Type II; International Code Council (ICC) Section
R703.8 Flashing; NFPA 285 Listed Component.

AAMA 714-15 Specified for Liquid - Applied Flashing

Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906
220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213
1451 Jacobson Avenue, Ashland, OH 44805 // Phone: 419.289.2050 // 800.321.6457

1117/D100SD

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ALMOND - 30 ctg cs
Material: 965724C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.29 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.45 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Light beige
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.82 mg/kg
Dermal	
Product:	ATEmix: 4,959.97 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Diocetyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ALMOND - 30 ctg cs
Material: 965724C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.29 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.45 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Light beige
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.82 mg/kg
Dermal	
Product:	ATEmix: 4,959.97 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.**16. Other information, including date of preparation or last revision****Revision Date:** 10/06/2015**Version #:** 1.0**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ALUMINUM STONE - 30 CTG CS

Material: 965851C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants

3735 Green Road

Beachwood OH 44122

US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	26.12 %
Acute toxicity, dermal	29.13 %
Acute toxicity, inhalation, vapor	97.81 %
Acute toxicity, inhalation, dust or mist	96.82 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.22 %
Chronic hazards to the aquatic environment	97.84 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Decanedioic acid ester	52829-07-9	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

- General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters
Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

			2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

			Environment) (12 2008)
Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stearic acid	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	0.2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Dust and fume. - as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Amorphous silica - Total	TWA	4 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zirconium dioxide - as Zr	STEL	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zirconium dioxide - as Zr	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aromatic petroleum distillates	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	Not classified for acute toxicity based on available data.
Dermal	
Product:	Not classified for acute toxicity based on available data.
Inhalation	
Product:	ATEmix: 15.33 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product:	No data available.

Serious Eye Damage/Eye Irritation

Product:	No data available.

Respiratory or Skin Sensitization

Product:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product:	No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity

Product:	No data available.

Specific Target Organ Toxicity - Single Exposure

Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:	No data available.

Aspiration Hazard

Product:	No data available.

Other effects:	No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish Product:	No data available.

Aquatic Invertebrates**Product:** No data available.**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log K_{ow})****Product:** No data available.**Mobility in soil:**

No data available.

Other adverse effects:

Harmful to aquatic organisms.

13. Disposal considerations**Disposal instructions:**

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging:

No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Decanedioic acid ester	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations
US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide	Carcinogenic. 09 2011
Diisodecyl phthalate	Developmental toxin. 09 2011
Ethylbenzene	Carcinogenic. 09 2011
Carbon Black	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011

Methanol	Developmental toxin. 03 2012
Benzene	Carcinogenic. 09 2011
Benzene	Developmental toxin. 09 2011
Benzene	Male reproductive toxin. 09 2011

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : Not available.

VOC Method 310 : Not available.

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 06/08/2018

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ALUMINUM STONE - 30 CTG CS

Material: 965851C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	26.12 %
Acute toxicity, dermal	29.13 %
Acute toxicity, inhalation, vapor	97.81 %
Acute toxicity, inhalation, dust or mist	96.82 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.22 %
Chronic hazards to the aquatic environment	97.84 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Decanedioic acid ester	52829-07-9	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

- General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters
Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

			2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

			Environment) (12 2008)
Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stearic acid	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	0.2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume. - as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Dust and fume. - as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Amorphous silica - Total	TWA	4 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zirconium dioxide - as Zr	STEL	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zirconium dioxide - as Zr	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aromatic petroleum distillates	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	Not classified for acute toxicity based on available data.
Dermal	
Product:	Not classified for acute toxicity based on available data.
Inhalation	
Product:	ATEmix: 15.33 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product:	No data available.

Serious Eye Damage/Eye Irritation

Product:	No data available.

Respiratory or Skin Sensitization

Product:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product:	No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity

Product:	No data available.

Specific Target Organ Toxicity - Single Exposure

Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:	No data available.

Aspiration Hazard

Product:	No data available.

Other effects:	No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish Product:	No data available.

Aquatic Invertebrates**Product:** No data available.**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log K_{ow})****Product:** No data available.**Mobility in soil:**

No data available.

Other adverse effects:

Harmful to aquatic organisms.

13. Disposal considerations**Disposal instructions:**

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging:

No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Decanedioic acid ester	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations
US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide	Carcinogenic. 09 2011
Diisodecyl phthalate	Developmental toxin. 09 2011
Ethylbenzene	Carcinogenic. 09 2011
Carbon Black	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011

Methanol	Developmental toxin. 03 2012
Benzene	Carcinogenic. 09 2011
Benzene	Developmental toxin. 09 2011
Benzene	Male reproductive toxin. 09 2011

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : Not available.

VOC Method 310 : Not available.

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 06/08/2018

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ANODIZED ALUMINUM- 30 CTG CS
Material: 965878C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.32 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.18 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.36 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.51 mg/kg
Dermal	
Product:	ATEmix: 4,958.43 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ANODIZED ALUMINUM- 30 CTG CS
Material: 965878C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.32 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.18 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.36 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.51 mg/kg
Dermal	
Product:	ATEmix: 4,958.43 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BEIGE- 30 CTG CS
Material: 965808C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.2 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.21 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.71 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Beige
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,096.94 mg/kg
Dermal	
Product:	ATEmix: 4,966.6 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BEIGE- 30 CTG CS
Material: 965808C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.2 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.21 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.71 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Beige
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,096.94 mg/kg
Dermal	
Product:	ATEmix: 4,966.6 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BLACK - 30 ctg cs

Material: 965802C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.71 %
Acute toxicity, dermal	28.27 %
Acute toxicity, inhalation, vapor	97.94 %
Acute toxicity, inhalation, dust or mist	97.13 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	92.11 %
Chronic hazards to the aquatic environment	97.96 %

Label Elements

Hazard Symbol:



Signal Word:

Danger

Hazard Statement:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Toxic to aquatic life.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response:

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Diisodecyl phthalate	26761-40-0	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Carbon Black	1333-86-4	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters
Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air

Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to

			Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation

			296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Black

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Diisodecyl phthalate LD 50 (Rat): 64,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Carbon Black LD 50 (Rat): > 8,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Hydrotreated heavy
naphthenic distillate LD 50 (Rat): > 5,000 mg/kg

Stearic acid LD 50 (Rat): > 2,000 mg/kg

Dibutyl tin dilaurate LD 50 (Rat): 2,071 mg/kg

Iodopropynyl
butylcarbamate LD 50 (Rat): 1.1 g/kg**Dermal****Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Diisodecyl phthalate	
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate	10000 lbs
(Limestone)	
Diisodecyl phthalate	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Carbon Black
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Diisodecyl phthalate
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent) : 39 g/l
VOC Method 310 : 2.93 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 11/28/2018

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BLACK - 30 ctg cs

Material: 965802C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.71 %
Acute toxicity, dermal	28.27 %
Acute toxicity, inhalation, vapor	97.94 %
Acute toxicity, inhalation, dust or mist	97.13 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	92.11 %
Chronic hazards to the aquatic environment	97.96 %

Label Elements

Hazard Symbol:



Signal Word:

Danger

Hazard Statement:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Toxic to aquatic life.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response:

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Diisodecyl phthalate	26761-40-0	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Carbon Black	1333-86-4	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate -	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air

Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to

			Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation

			296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Black

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Diisodecyl phthalate LD 50 (Rat): 64,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Carbon Black LD 50 (Rat): > 8,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Hydrotreated heavy
naphthenic distillate LD 50 (Rat): > 5,000 mg/kg

Stearic acid LD 50 (Rat): > 2,000 mg/kg

Dibutyl tin dilaurate LD 50 (Rat): 2,071 mg/kg

Iodopropynyl
butylcarbamate LD 50 (Rat): 1.1 g/kg**Dermal****Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): $\geq 1,000$ mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Diisodecyl phthalate	
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate	10000 lbs
(Limestone)	
Diisodecyl phthalate	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Carbon Black
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Diisodecyl phthalate
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 39 g/l
VOC Method 310 : 2.93 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 11/28/2018

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BRONZE -15X600ML SSG CS
Material: 965801C385

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.32 %
Acute toxicity, dermal	27.82 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	67.03 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Bronze colored
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,110.21 mg/kg
Dermal	
Product:	ATEmix: 4,880.11 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.

Specified substance(s):

Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Xylene	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>), 24 h): 11 - 18 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (<i>Leuciscus idus</i>), 48 h): 2 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (<i>Daphnia magna</i>), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:
Fish
Product: No data available.

Specified substance(s):

Xylene	NOAEL (<i>Oncorhynchus mykiss</i> , 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (<i>Oncorhynchus mykiss</i> , 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (<i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
Iron oxide	LOAEL (<i>Pimephales promelas</i> , 33 d): 1.6 mg/l experimental result
Carbon Black	NOAEL (<i>Salmo</i> sp., 30 d): 17 mg/l QSAR

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability
Biodegradation
Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Iron oxide	500 lbs
Carbon Black	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diocetyl phthalate

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate

US. Rhode Island RTK**Chemical Identity**

Xylene
Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BRONZE -15X600ML SSG CS
Material: 965801C385

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person: EH&S Department
Telephone: 1-800-263-6046
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.32 %
Acute toxicity, dermal	27.82 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	67.03 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Bronze colored
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,110.21 mg/kg
Dermal	
Product:	ATEmix: 4,880.11 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish Product:	No data available.

Specified substance(s):

Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Xylene	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>), 24 h): 11 - 18 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (<i>Leuciscus idus</i>), 48 h): 2 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (<i>Daphnia magna</i>), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:
Fish
Product: No data available.

Specified substance(s):

Xylene	NOAEL (<i>Oncorhynchus mykiss</i> , 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (<i>Oncorhynchus mykiss</i> , 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (<i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
Iron oxide	LOAEL (<i>Pimephales promelas</i> , 33 d): 1.6 mg/l experimental result
Carbon Black	NOAEL (<i>Salmo</i> sp., 30 d): 17 mg/l QSAR

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability
Biodegradation
Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Iron oxide	500 lbs
Carbon Black	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diocetyl phthalate

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate

US. Rhode Island RTK**Chemical Identity**

Xylene
Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BUFF - 30 CTG CS
Material: 965807C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.23 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.21 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.64 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Tan
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,098.84 mg/kg
Dermal	
Product:	ATEmix: 4,964.41 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Copper phthalocyanine	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 BUFF - 30 CTG CS
Material: 965807C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.23 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.21 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.64 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Tan
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,098.84 mg/kg
Dermal	
Product:	ATEmix: 4,964.41 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Copper phthalocyanine	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 DARK BRONZE - 30 ctg cs
Material: 965721C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.19 %
Acute toxicity, dermal	27.84 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.88 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Dark brown
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,102.78 mg/kg
Dermal	
Product:	ATEmix: 4,870.28 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.

Specified substance(s):

Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Xylene	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>), 24 h): 11 - 18 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (<i>Leuciscus idus</i>), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (<i>Daphnia magna</i>), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	NOAEL (<i>Oncorhynchus mykiss</i> , 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (<i>Oncorhynchus mykiss</i> , 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (<i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
Carbon Black	NOAEL (<i>Salmo</i> sp., 30 d): 17 mg/l QSAR
Iron oxide	LOAEL (<i>Pimephales promelas</i> , 33 d): 1.6 mg/l experimental result

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Carbon Black	500 lbs
Iron oxide	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diocetyl phthalate

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate

US. Rhode Island RTK**Chemical Identity**

Xylene
Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	2.99 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 DARK BRONZE - 30 ctg cs
Material: 965721C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person: EH&S Department
Telephone: 1-800-263-6046
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.19 %
Acute toxicity, dermal	27.84 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.88 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Dark brown
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,102.78 mg/kg
Dermal	
Product:	ATEmix: 4,870.28 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.

Specified substance(s):

Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Xylene	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 70 - 149 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (<i>Lepomis macrochirus</i>), 24 h): 66 - 276 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>), 24 h): 11 - 18 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (<i>Leuciscus idus</i>), 48 h): 2 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (<i>Daphnia magna</i>), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:
Fish
Product: No data available.

Specified substance(s):

Xylene	NOAEL (<i>Oncorhynchus mykiss</i> , 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (<i>Oncorhynchus mykiss</i> , 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (<i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
Carbon Black	NOAEL (<i>Salmo</i> sp., 30 d): 17 mg/l QSAR
Iron oxide	LOAEL (<i>Pimephales promelas</i> , 33 d): 1.6 mg/l experimental result

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability
Biodegradation
Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Carbon Black	500 lbs
Iron oxide	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diocetyl phthalate

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate

US. Rhode Island RTK**Chemical Identity**

Xylene
Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	2.99 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 GRAY - 30 CTG CS
Material: 965712C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.31 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.25 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.38 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 5,888.84 mg/kg
Dermal	
Product:	ATEmix: 4,959.05 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Aquatic Invertebrates	
Product:	No data available.
Specified substance(s):	
Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish	
Product:	No data available.
Specified substance(s):	
Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Titanium dioxide	LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates	
Product:	No data available.

Toxicity to Aquatic Plants	
Product:	No data available.

Persistence and Degradability

Biodegradation	
Product:	No data available.

BOD/COD Ratio	
Product:	No data available.

Bioaccumulative Potential Bioconcentration Factor (BCF)

Product:	No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 GRAY - 30 CTG CS
Material: 965712C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.31 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.25 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.38 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 5,888.84 mg/kg
Dermal	
Product:	ATEmix: 4,959.05 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 GRAY STONE - 30 CTG CS
Material: 965852C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.27 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.43 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,094.56 mg/kg
Dermal	
Product:	ATEmix: 4,961.88 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

**Bioaccumulative Potential
Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Copper phthalocyanine	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Diocetyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 GRAY STONE - 30 CTG CS
Material: 965852C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.27 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.43 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,094.56 mg/kg
Dermal	
Product:	ATEmix: 4,961.88 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Copper phthalocyanine	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Diocetyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 HARTFORD GREEN - 30 CS

Material: 965824C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.33 %
Acute toxicity, dermal	27.72 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.95 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Green
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	ATEmix: 5,918.8 mg/kg
Dermal	
Product:	ATEmix: 4,879.3 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate

LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR
Carbon Black	NOAEL (Salmo sp., 30 d): 17 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**Chemical Identity**

Polyvinyl chloride

OSHA hazard(s)Blood
Liver
Cancer
Flammability
Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Diethyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Copper phthalocyanine	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Diethyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate (Limestone)	500 lbs
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Carbon Black	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black**US. Massachusetts RTK - Substance List****Chemical Identity**Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diethyl phthalate**US. Pennsylvania RTK - Hazardous Substances****Chemical Identity**Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate**US. Rhode Island RTK****Chemical Identity**Xylene
Diisodecyl phthalate**Other Regulations:**

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or exempt from the Inventory.

EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision**Revision Date:** 10/06/2015**Version #:** 1.0**Further Information:** No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 HARTFORD GREEN - 30 CS
Material: 965824C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.33 %
Acute toxicity, dermal	27.72 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.26 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.95 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Green
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.

Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	ATEmix: 5,918.8 mg/kg
Dermal	
Product:	ATEmix: 4,879.3 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate

LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR
Carbon Black	NOAEL (Salmo sp., 30 d): 17 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.**Other Adverse Effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**Chemical Identity**

Polyvinyl chloride

OSHA hazard(s)Blood
Liver
Cancer
Flammability
Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Diethyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Copper phthalocyanine	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Diethyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate (Limestone)	500 lbs
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Carbon Black	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate
Carbon Black**US. Massachusetts RTK - Substance List****Chemical Identity**Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand
Diethyl phthalate**US. Pennsylvania RTK - Hazardous Substances****Chemical Identity**Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Diisodecyl phthalate**US. Rhode Island RTK****Chemical Identity**Xylene
Diisodecyl phthalate**Other Regulations:**

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or exempt from the Inventory.

EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 IVORY- 30 CTG CS
Material: 965858C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.3 %
Acute toxicity, dermal	28.4 %
Acute toxicity, inhalation, vapor	97.79 %
Acute toxicity, inhalation, dust or mist	96.78 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.05 %
Chronic hazards to the aquatic environment	97.81 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.01 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl	TWA	1 ppm	US. OSHA Specifically Regulated Substances

chloride monomer			(29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)

	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Titanium dioxide	ST ESL		50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Titanium dioxide - Total dust.	TWA PEL		10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Titanium dioxide - Respirable fraction.	TWA PEL		5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA		20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL		100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA		0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL		500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stearic acid - Respirable fraction.	TWA		3 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid - Inhalable fraction.	TWA		10 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid	ST ESL		1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	ST ESL		50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Dibutyl tin dilaurate - as Sn	STEL		0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA		0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

Contaminants (29 CFR 1910.1000) (02 2006)			
Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide	TWA	10 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste

Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 108,882.56 mg/kg

Dermal

Product: ATEmix: 4,952.31 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Diisodecyl phthalate LC 50 (Rat): > 12.54 mg/l

Isophorone Diisocyanate LC 50 (Rat): 135 - 160 mg/m3

Hydrotreated heavy
naphthenic distillate LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation**Product:** No data available.**Specified substance(s):**

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Titanium dioxide	LC 50 (Pimephales promelas, 96 h): 8.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.5 - 11 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Water flea (Daphnia magna), 48 h): > 0.02 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Stearic acid	EC 50 (Daphnia magna, 48 h): > 4.8 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Stearic acid	EC 50 (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study LOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study NOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)
Product: No data available.

Specified substance(s):

Titanium dioxide	Cyprinus carpio, Bioconcentration Factor (BCF): 16 Aquatic sediment Experimental result, Supporting study Bioconcentration Factor (BCF): 0.16 Terrestrial Experimental result, Supporting study Cyprinus carpio, Bioconcentration Factor (BCF): 9 Aquatic sediment Experimental result, Supporting study Cyprinus carpio, Bioconcentration Factor (BCF): 8 Aquatic sediment Experimental result, Supporting study Oncorhynchus mykiss, Bioconcentration Factor (BCF): 58 Aquatic sediment Experimental result, Key study
Stearic acid	Danio rerio, Bioconcentration Factor (BCF): 236 - 282 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study Danio rerio, Bioconcentration Factor (BCF): 238 - 288 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study Danio rerio, Bioconcentration Factor (BCF): 234 - 249 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in soil: No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide	Carcinogenic. 09 2011
Ethylbenzene	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Dioctyl phthalate	Carcinogenic. 09 2011
Dioctyl phthalate	Developmental toxin. 09 2011
Dioctyl phthalate	Male reproductive toxin. 09 2011
Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011
Carbon Black	Carcinogenic. 09 2011
Methanol	Developmental toxin. 03 2012

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l

VOC Method 310 : 3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 04/21/2017

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 IVORY- 30 CTG CS
Material: 965858C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.3 %
Acute toxicity, dermal	28.4 %
Acute toxicity, inhalation, vapor	97.79 %
Acute toxicity, inhalation, dust or mist	96.78 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.05 %
Chronic hazards to the aquatic environment	97.81 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.01 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl	TWA	1 ppm	US. OSHA Specifically Regulated Substances

chloride monomer			(29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)

	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Titanium dioxide	ST ESL		50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Titanium dioxide - Total dust.	TWA PEL		10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Titanium dioxide - Respirable fraction.	TWA PEL		5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stearic acid - Respirable fraction.	TWA		3 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid - Inhalable fraction.	TWA		10 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid	ST ESL		1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	ST ESL		50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL		5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Dibutyl tin dilaurate - as Sn	STEL		0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA		0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

Contaminants (29 CFR 1910.1000) (02 2006)			
Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide	TWA	10 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste

Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 108,882.56 mg/kg

Dermal

Product: ATEmix: 4,952.31 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Diisodecyl phthalate LC 50 (Rat): > 12.54 mg/l

Isophorone Diisocyanate LC 50 (Rat): 135 - 160 mg/m3

Hydrotreated heavy
naphthenic distillate LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation**Product:** No data available.**Specified substance(s):**

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Titanium dioxide	LC 50 (Pimephales promelas, 96 h): 8.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.5 - 11 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Water flea (Daphnia magna), 48 h): > 0.02 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Stearic acid	EC 50 (Daphnia magna, 48 h): > 4.8 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Stearic acid	EC 50 (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study LOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study NOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)
Product: No data available.

Specified substance(s):

Titanium dioxide	Cyprinus carpio, Bioconcentration Factor (BCF): 16 Aquatic sediment Experimental result, Supporting study Bioconcentration Factor (BCF): 0.16 Terrestrial Experimental result, Supporting study Cyprinus carpio, Bioconcentration Factor (BCF): 9 Aquatic sediment Experimental result, Supporting study Cyprinus carpio, Bioconcentration Factor (BCF): 8 Aquatic sediment Experimental result, Supporting study Oncorhynchus mykiss, Bioconcentration Factor (BCF): 58 Aquatic sediment Experimental result, Key study
Stearic acid	Danio rerio, Bioconcentration Factor (BCF): 236 - 282 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study Danio rerio, Bioconcentration Factor (BCF): 238 - 288 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study Danio rerio, Bioconcentration Factor (BCF): 234 - 249 Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in soil: No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide	Carcinogenic. 09 2011
Ethylbenzene	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Dioctyl phthalate	Carcinogenic. 09 2011
Dioctyl phthalate	Developmental toxin. 09 2011
Dioctyl phthalate	Male reproductive toxin. 09 2011
Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011
Carbon Black	Carcinogenic. 09 2011
Methanol	Developmental toxin. 03 2012

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l

VOC Method 310 : 3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 04/21/2017

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 LIGHT BRONZE- 30 CT CS
Material: 965809C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.11 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.23 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.83 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)

Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Bronze colored
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,091.29 mg/kg
Dermal	
Product:	ATEmix: 4,972.39 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity	
Product:	No data available.

Skin Corrosion/Irritation	
Product:	No data available.

Serious Eye Damage/Eye Irritation	
Product:	No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy
naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride
Cancer

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:
Acute hazards to the aquatic environment:
Fish

Product: No data available.

Specified substance(s):

Calcium carbonate LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Ethylbenzene
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Titanium dioxide LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene LC 50 (Water flea (*Daphnia magna*), 24 h): > 100 - 1,000 mg/l Mortality

Ethylbenzene
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.53 - 3.17 mg/l Intoxication

Titanium dioxide EC 50 (Water flea (*Daphnia magna*), 48 h): > 1,000 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (*Daphnia magna*), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:**Fish**

Product: No data available.

Specified substance(s):

Xylene NOAEL (*Oncorhynchus mykiss*, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (*Oncorhynchus mykiss*, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (*Coregonus autumnalis migratorius* G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (*Oncorhynchus mykiss*, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability**Biodegradation**

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential**Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.

Other Adverse Effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate (Limestone)	500 lbs
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Titanium dioxide	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date:	10/06/2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 LIGHT BRONZE- 30 CT CS

Material: 965809C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:

Telephone:

Emergency telephone number:

EH&S Department

1-800-263-6046

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.11 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.23 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.83 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)

Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste
Color: Bronze colored

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,091.29 mg/kg
Dermal	
Product:	ATEmix: 4,972.39 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity	
Product:	No data available.

Skin Corrosion/Irritation	
Product:	No data available.

Serious Eye Damage/Eye Irritation	
Product:	No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride
Cancer

Germ Cell Mutagenicity

In vitro Product: No data available.

In vivo Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:
Acute hazards to the aquatic environment:
Fish

Product: No data available.

Specified substance(s):

Calcium carbonate LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Ethylbenzene
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Titanium dioxide LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene LC 50 (Water flea (*Daphnia magna*), 24 h): > 100 - 1,000 mg/l Mortality

Ethylbenzene
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (*Daphnia magna*), 24 h): 1.53 - 3.17 mg/l Intoxication

Titanium dioxide EC 50 (Water flea (*Daphnia magna*), 48 h): > 1,000 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (*Daphnia magna*), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (*Oncorhynchus mykiss*, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (*Oncorhynchus mykiss*, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (*Coregonus autumnalis migratorius* G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (*Oncorhynchus mykiss*, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.

Other Adverse Effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Delayed (Chronic) Health Hazard

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate (Limestone)	500 lbs
Xylene	500 lbs
Calcium oxide	500 lbs
Ethylbenzene	500 lbs
Titanium dioxide	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date:	10/06/2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 LIMESTONE - 30 ctg cs

Material: 965805C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	26.12 %
Acute toxicity, dermal	29.17 %
Acute toxicity, inhalation, vapor	97.81 %
Acute toxicity, inhalation, dust or mist	96.92 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.21 %
Chronic hazards to the aquatic environment	97.84 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate -	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air

Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor -

			Regulation Respecting the Quality of the Work Environment) (09 2017)
Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Amorphous silica - Total	TWA	4 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste
Color: Grey-yellowish

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Diisodecyl phthalate LD 50 (Rat): 64,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Hydrotreated heavy
naphthenic distillate LD 50 (Rat): > 5,000 mg/kg

Stearic acid LD 50 (Rat): > 2,000 mg/kg

Dibutyl tin dilaurate LD 50 (Rat): 2,071 mg/kg

Iodopropynyl
butylcarbamate LD 50 (Rat): 1.1 g/kg**Dermal****Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide	LC 50 (Rat): 3.43 mg/l
Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity**Product:**

No data available.

Skin Corrosion/Irritation**Product:**

No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l
VOC Method 310 : 2.99 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 01/31/2019

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 LIMESTONE - 30 ctg cs

Material: 965805C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	26.12 %
Acute toxicity, dermal	29.17 %
Acute toxicity, inhalation, vapor	97.81 %
Acute toxicity, inhalation, dust or mist	96.92 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.21 %
Chronic hazards to the aquatic environment	97.84 %

Label Elements

Hazard Symbol:



Signal Word:

Danger

Hazard Statement:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response:

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate -	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air

Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor -

			Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste
Color: Grey-yellowish

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Diisodecyl phthalate LD 50 (Rat): 64,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Hydrotreated heavy
naphthenic distillate LD 50 (Rat): > 5,000 mg/kg

Stearic acid LD 50 (Rat): > 2,000 mg/kg

Dibutyl tin dilaurate LD 50 (Rat): 2,071 mg/kg

Iodopropynyl
butylcarbamate LD 50 (Rat): 1.1 g/kg**Dermal****Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide	LC 50 (Rat): 3.43 mg/l
Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity**Product:**

No data available.

Skin Corrosion/Irritation**Product:**

No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations**US. California Proposition 65****WARNING**

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l
VOC Method 310 : 2.99 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 01/31/2019

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 NATURAL CLAY - 30 CS
Material: 965856C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.23 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.2 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.55 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,089.66 mg/kg
Dermal	
Product:	ATEmix: 4,964.09 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

**Bioaccumulative Potential
Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 NATURAL CLAY - 30 CS
Material: 965856C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.23 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.2 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.55 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,089.66 mg/kg
Dermal	
Product:	ATEmix: 4,964.09 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

**Bioaccumulative Potential
Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 OFF WHITE - 30 CTG CS
Material: 965803C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.3 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.41 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,085.09 mg/kg
Dermal	
Product:	ATEmix: 4,959.57 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

**Bioaccumulative Potential
Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Diocetyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 OFF WHITE - 30 CTG CS
Material: 965803C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.3 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.41 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,085.09 mg/kg
Dermal	
Product:	ATEmix: 4,959.57 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.**16. Other information, including date of preparation or last revision****Revision Date:** 10/06/2015**Version #:** 1.0**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 PRECAST WHITE - 30 CS
Material: 965811C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.31 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.18 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.39 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.21 mg/kg
Dermal	
Product:	ATEmix: 4,958.62 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Aquatic Invertebrates	
Product:	No data available.
Specified substance(s):	
Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish	
Product:	No data available.
Specified substance(s):	
Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Titanium dioxide	LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates	
Product:	No data available.

Toxicity to Aquatic Plants	
Product:	No data available.

Persistence and Degradability

Biodegradation	
Product:	No data available.

BOD/COD Ratio	
Product:	No data available.

Bioaccumulative Potential Bioconcentration Factor (BCF)

Product:	No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 PRECAST WHITE - 30 CS

Material: 965811C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:

Telephone:

Emergency telephone number:

EH&S Department

1-800-263-6046

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.31 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.18 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.39 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,084.21 mg/kg
Dermal	
Product:	ATEmix: 4,958.62 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Aquatic Invertebrates	
Product:	No data available.
Specified substance(s):	
Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish	
Product:	No data available.
Specified substance(s):	
Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result
Calcium oxide	NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted
Titanium dioxide	LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates	
Product:	No data available.

Toxicity to Aquatic Plants	
Product:	No data available.

Persistence and Degradability

Biodegradation	
Product:	No data available.

BOD/COD Ratio	
Product:	No data available.

Bioaccumulative Potential Bioconcentration Factor (BCF)

Product:	No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 REDWOOD TAN - 30 CG CS

Material: 965804C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.3 %
Acute toxicity, dermal	28.24 %
Acute toxicity, inhalation, vapor	97.79 %
Acute toxicity, inhalation, dust or mist	96.81 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.6 %
Chronic hazards to the aquatic environment	97.81 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Diisodecyl phthalate	26761-40-0	0.01 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Titanium dioxide	13463-67-7	0.1 - <1%
Iron oxide	1309-37-1	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

- General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters
Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

			2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Titanium dioxide	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Titanium dioxide - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Titanium dioxide - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stearic acid - Respirable	TWA	3 mg/m3	US. ACGIH Notice of Intended Changes (NIC)

fraction.			to Threshold Limit Values (03 2016)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid	ST ESL	1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values		Source
Calcium carbonate - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)

Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide	TWA	10 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Tan

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.
Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product: ATEmix: 108,885.76 mg/kg

Dermal Product: ATEmix: 4,963.43 mg/kg

Inhalation Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Titanium dioxide	LC 50 (Rat): 3.43 mg/l
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Iron oxide	in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating

Hydrotreated heavy
naphthenic distillate

Rabbit, 24 hrs: Not irritating

Stearic acid

Rabbit, 27 - 72 hrs: Not irritating

Dibutyl tin dilaurate

Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization**Product:**May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:**

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene

Overall evaluation: Possibly carcinogenic to humans.

Titanium dioxide

Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy
naphthenic distillateOverall evaluation: Not classifiable as to carcinogenicity to humans. Overall
evaluation: Carcinogenic to humans.**US. National Toxicology Program (NTP) Report on Carcinogens:**Hydrotreated heavy
naphthenic distillate

Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity**In vitro****Product:**

No data available.

In vivo**Product:**

No data available.

Reproductive toxicity**Product:**

No data available.

Specific Target Organ Toxicity - Single Exposure**Product:**

No data available.

Specific Target Organ Toxicity - Repeated Exposure**Product:**

No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.5 - 11 mg/l Mortality
Titanium dioxide	LC 50 (Pimephales promelas, 96 h): 8.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	EC 50 (Water flea (Daphnia magna), 48 h): > 0.02 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Stearic acid	EC 50 (Daphnia magna, 48 h): > 4.8 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Stearic acid

EC 50 (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study
LOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study
NOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.

BOD/COD Ratio

Product:

No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:

No data available.

Specified substance(s):

Titanium dioxide

Cyprinus carpio, Bioconcentration Factor (BCF): 16 Aquatic sediment
Experimental result, Supporting study
Bioconcentration Factor (BCF): 0.16 Terrestrial Experimental result,
Supporting study
Cyprinus carpio, Bioconcentration Factor (BCF): 9 Aquatic sediment
Experimental result, Supporting study
Cyprinus carpio, Bioconcentration Factor (BCF): 8 Aquatic sediment
Experimental result, Supporting study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): 58 Aquatic sediment
Experimental result, Key study

Stearic acid

Danio rerio, Bioconcentration Factor (BCF): 236 - 282 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study
Danio rerio, Bioconcentration Factor (BCF): 238 - 288 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study
Danio rerio, Bioconcentration Factor (BCF): 234 - 249 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study

Partition Coefficient n-octanol / water (log Kow)

Product:

No data available.

Specified substance(s):

Xylene

Log Kow: 3.12 - 3.20

Ethylbenzene

Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**Chemical Identity**

Polyvinyl chloride

OSHA hazard(s)Blood
Liver
Cancer
Flammability
Central nervous systemCrystalline Silica
(Quartz)/ Silica Sandkidney effects
lung effects
immune system effects
Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Titanium dioxide	10000 lbs
Iron oxide	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**Chemical Identity**

Xylene

Reportable quantity

Reportable quantity: lbs.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Ethylbenzene	Carcinogenic. 09 2011
Titanium dioxide	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Carbon Black	Carcinogenic. 09 2011
Crystalline Silica (Quartz)/	Carcinogenic. 09 2011
Silica Sand	
Methanol	Developmental toxin. 03 2012

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene

International regulations**Montreal protocol**

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l

VOC Method 310 : 3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 04/21/2017

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 REDWOOD TAN - 30 CG CS

Material: 965804C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.3 %
Acute toxicity, dermal	28.24 %
Acute toxicity, inhalation, vapor	97.79 %
Acute toxicity, inhalation, dust or mist	96.81 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	93.6 %
Chronic hazards to the aquatic environment	97.81 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	1 - <5%
Xylene	1330-20-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Diisodecyl phthalate	26761-40-0	0.01 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Titanium dioxide	13463-67-7	0.1 - <1%
Iron oxide	1309-37-1	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

- General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters
Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

			2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Titanium dioxide	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Titanium dioxide - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Titanium dioxide - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Iron oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stearic acid - Respirable	TWA	3 mg/m3	US. ACGIH Notice of Intended Changes (NIC)

fraction.			to Threshold Limit Values (03 2016)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2016)
Stearic acid	ST ESL	1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (03 2014)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)

Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide	TWA	10 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Tan

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.
Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product: ATEmix: 108,885.76 mg/kg

Dermal Product: ATEmix: 4,963.43 mg/kg

Inhalation Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Diisodecyl phthalate LC 50 (Rat): > 12.54 mg/l

Isophorone Diisocyanate LC 50 (Rat): 135 - 160 mg/m3

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Hydrotreated heavy naphthenic distillate LC 50 (Rat): 9.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate in vivo (Rabbit): Not irritant Experimental result, Key study

Xylene in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study

Titanium dioxide in vivo (Rabbit): Not irritant Experimental result, Supporting study

Iron oxide in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study

Hydrotreated heavy naphthenic distillate in vivo (Rabbit): Not irritant Experimental result, Key study

Stearic acid in vivo (Rabbit): Not irritant Experimental result, Key study

Dibutyl tin dilaurate In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate Rabbit, 24 - 72 hrs: Not irritating

Xylene Rabbit, 24 hrs: Moderately irritating

Ethylbenzene Rabbit, 7 d: Slightly irritating

Titanium dioxide Rabbit, 24 hrs: Not irritating

Hydrotreated heavy
naphthenic distillate

Rabbit, 24 hrs: Not irritating

Stearic acid

Rabbit, 27 - 72 hrs: Not irritating

Dibutyl tin dilaurate

Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization**Product:**May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:**

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene

Overall evaluation: Possibly carcinogenic to humans.

Titanium dioxide

Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy
naphthenic distillateOverall evaluation: Not classifiable as to carcinogenicity to humans. Overall
evaluation: Carcinogenic to humans.**US. National Toxicology Program (NTP) Report on Carcinogens:**Hydrotreated heavy
naphthenic distillate

Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity**In vitro****Product:**

No data available.

In vivo**Product:**

No data available.

Reproductive toxicity**Product:**

No data available.

Specific Target Organ Toxicity - Single Exposure**Product:**

No data available.

Specific Target Organ Toxicity - Repeated Exposure**Product:**

No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.5 - 11 mg/l Mortality
Titanium dioxide	LC 50 (Pimephales promelas, 96 h): 8.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Diisodecyl phthalate	EC 50 (Water flea (Daphnia magna), 48 h): > 0.02 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Stearic acid	EC 50 (Daphnia magna, 48 h): > 4.8 mg/l Read-across based on grouping of substances (category approach), Weight of Evidence study
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Stearic acid

EC 50 (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study
LOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study
NOAEL (Daphnia magna, 21 d): > 0.22 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.

BOD/COD Ratio

Product:

No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:

No data available.

Specified substance(s):

Titanium dioxide

Cyprinus carpio, Bioconcentration Factor (BCF): 16 Aquatic sediment
Experimental result, Supporting study
Bioconcentration Factor (BCF): 0.16 Terrestrial Experimental result,
Supporting study
Cyprinus carpio, Bioconcentration Factor (BCF): 9 Aquatic sediment
Experimental result, Supporting study
Cyprinus carpio, Bioconcentration Factor (BCF): 8 Aquatic sediment
Experimental result, Supporting study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): 58 Aquatic sediment
Experimental result, Key study

Stearic acid

Danio rerio, Bioconcentration Factor (BCF): 236 - 282 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study
Danio rerio, Bioconcentration Factor (BCF): 238 - 288 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study
Danio rerio, Bioconcentration Factor (BCF): 234 - 249 Aquatic sediment
Read-across from supporting substance (structural analogue or surrogate),
Key study

Partition Coefficient n-octanol / water (log Kow)

Product:

No data available.

Specified substance(s):

Xylene

Log Kow: 3.12 - 3.20

Ethylbenzene

Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**Chemical Identity**

Polyvinyl chloride

OSHA hazard(s)Blood
Liver
Cancer
Flammability
Central nervous systemCrystalline Silica
(Quartz)/ Silica Sandkidney effects
lung effects
immune system effects
Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Calcium oxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Titanium dioxide	10000 lbs
Iron oxide	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Dibutyl tin dilaurate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**Chemical Identity**

Xylene

Reportable quantity

Reportable quantity: lbs.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Ethylbenzene	Carcinogenic. 09 2011
Titanium dioxide	Carcinogenic. 09 2011
Toluene	Developmental toxin. 09 2011
Carbon Black	Carcinogenic. 09 2011
Crystalline Silica (Quartz)/	Carcinogenic. 09 2011
Silica Sand	
Methanol	Developmental toxin. 03 2012

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene

International regulations**Montreal protocol**

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 40 g/l

VOC Method 310 : 3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 04/21/2017

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 SANDALWOOD - 30 CTG CS
Material: 965862C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.25 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.2 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.54 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:	May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Tan
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,090.02 mg/kg
Dermal	
Product:	ATEmix: 4,962.85 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

**Bioaccumulative Potential
Bioconcentration Factor (BCF)**

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 SANDALWOOD - 30 CTG CS
Material: 965862C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person: EH&S Department
Telephone: 1-800-263-6046
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.25 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.2 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.54 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Tan
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,090.02 mg/kg
Dermal	
Product:	ATEmix: 4,962.85 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 STONE - 30 CTG CS
Material: 965892C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.28 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.48 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Dark gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,088.05 mg/kg
Dermal	
Product:	ATEmix: 4,961.05 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 STONE - 30 CTG CS
Material: 965892C323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.28 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.19 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2

Unknown toxicity - Environment

Acute hazards to the aquatic environment	66.48 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Toxic to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage
Precautions for safe handling:

Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection
Control Parameters
Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
	OSHA_A CT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational

			Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWAEV	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Dark gray
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	1.3297
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 45,088.05 mg/kg
Dermal	
Product:	ATEmix: 4,961.05 mg/kg
Inhalation	
Product:	No data available.

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Calcium oxide	in vivo (Rabbit, 1 hrs): Irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	Irritating
Isophorone Diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 1
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Stearic acid	in vivo (Rabbit, 27 - 72 hrs): Not irritating
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Calcium carbonate

LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Xylene

LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 13.41 mg/l Mortality

Titanium dioxide

LC 50 (Mummichog (*Fundulus heteroclitus*), 96 h): > 1,000 mg/l Mortality

Ethylbenzene

LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 70 - 149 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 112 - 170 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 113 - 162 mg/l Mortality
LC 50 (Bluegill (*Lepomis macrochirus*), 24 h): 66 - 276 mg/l Mortality
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 24 h): 11 - 18 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates
Product:**

No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene
EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication
EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates
Product:**

No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Stearic acid	Log Kow: 8.23
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil:	No data available.
Other Adverse Effects:	Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information**TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information**US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Toluene	1000 lbs.
Diisodecyl phthalate (mixed Is)	
Dioctyl phthalate	100 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	500 lbs
Polyvinyl chloride	500 lbs
Calcium Carbonate	500 lbs
(Limestone)	
Xylene	500 lbs
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Ethylbenzene	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Stearic acid	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)**Chemical Identity**

Xylene
Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide
Isophorone Diisocyanate
Dioctyl phthalate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK**Chemical Identity**

Xylene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	40 g/l
VOC Method 310:	3.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are
not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 WHITE - 30 CTG**Material:** 965806C323**Recommended use and restriction on use****Recommended use:** Sealant**Restrictions on use:** Not known.**Manufacturer/Importer/Supplier/Distributor Information**Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US**Contact person:**

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification**Health Hazards**

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.67 %
Acute toxicity, dermal	29.84 %
Acute toxicity, inhalation, vapor	97.77 %
Acute toxicity, inhalation, dust or mist	96.82 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	91.64 %
Chronic hazards to the aquatic environment	97.79 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Aluminum oxide	1344-28-1	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values		Source
Calcium carbonate - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)

Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Amorphous silica - Total	TWA	4 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: White

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rat): 3,523 mg/kg
Titanium dioxide	LD 50 (Rat): > 5,000 mg/kg
Diisodecyl phthalate	LD 50 (Rat): 64,000 mg/kg
Ethylbenzene	LD 50 (Rat): 3,500 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): 4,814 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rat): > 5,000 mg/kg
Stearic acid	LD 50 (Rat): > 2,000 mg/kg
Aluminum oxide	LD 50 (Rat): > 10,000 mg/kg
Dibutyl tin dilaurate	LD 50 (Rat): 2,071 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rat): 1.1 g/kg

Dermal**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product:

Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide	LC 50 (Rat): 3.43 mg/l
Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l
Aluminum oxide	LC 50 (Rat): 7.6 mg/l

Repeated dose toxicity

Product:

No data available.

Skin Corrosion/Irritation

Product:

No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Diisodecyl phthalate (mixed Is)	
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Titanium dioxide	10000 lbs
Calcium oxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Aluminum oxide	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Calcium oxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 39 g/l
VOC Method 310 : 2.94 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 02/19/2019

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 WHITE - 30 CTG

Material: 965806C323

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.67 %
Acute toxicity, dermal	29.84 %
Acute toxicity, inhalation, vapor	97.77 %
Acute toxicity, inhalation, dust or mist	96.82 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	91.64 %
Chronic hazards to the aquatic environment	97.79 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Calcium carbonate	471-34-1	20 - <50%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Xylene	1330-20-7	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Diisodecyl phthalate	26761-40-0	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Stearic acid	57-11-4	0.1 - <1%
Aluminum oxide	1344-28-1	0.1 - <1%
Dibutyl tin dilaurate	77-58-7	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values		Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m ³		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m ³		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)

Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Type	Exposure Limit Values		Source
Calcium carbonate - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stearic acid	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stearic acid	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: White

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water: Insoluble in water

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature: No data available.

Decomposition temperature: No data available.

Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rat): 3,523 mg/kg
Titanium dioxide	LD 50 (Rat): > 5,000 mg/kg
Diisodecyl phthalate	LD 50 (Rat): 64,000 mg/kg
Ethylbenzene	LD 50 (Rat): 3,500 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): 4,814 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rat): > 5,000 mg/kg
Stearic acid	LD 50 (Rat): > 2,000 mg/kg
Aluminum oxide	LD 50 (Rat): > 10,000 mg/kg
Dibutyl tin dilaurate	LD 50 (Rat): 2,071 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rat): 1.1 g/kg

Dermal**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Xylene	LD 50 (Rabbit): 12,126 mg/kg
Diisodecyl phthalate	LD 50 (Rabbit): > 3,160 mg/kg
Ethylbenzene	LD 50 (Rabbit): 17,800 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): > 7,000 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rabbit): > 5,000 mg/kg
Stearic acid	LD 50 (Rabbit): > 2,000 mg/kg
Iodopropynyl butylcarbamate	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide	LC 50 (Rat): 3.43 mg/l
Diisodecyl phthalate	LC 50 (Rat): > 12.54 mg/l
Isophorone Diisocyanate	LC 50 (Rat): 135 - 160 mg/m3
Hydrotreated heavy naphthenic distillate	LC 50 (Rat): 9.6 mg/l
Aluminum oxide	LC 50 (Rat): 7.6 mg/l

Repeated dose toxicity**Product:**

No data available.

Skin Corrosion/Irritation**Product:**

No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Stearic acid	in vivo (Rabbit): Not irritant Experimental result, Key study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Stearic acid	Rabbit, 27 - 72 hrs: Not irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride	Cancer

Germ Cell Mutagenicity

In vitro Product:	No data available.

In vivo Product:	No data available.

Reproductive toxicity Product:	No data available.

Specific Target Organ Toxicity - Single Exposure Product:	No data available.

Specific Target Organ Toxicity - Repeated Exposure Product:	No data available.

Aspiration Hazard Product:	No data available.

Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Diisodecyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Diisodecyl phthalate	EC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 0.08 mg/l Mortality
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio**Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.**Other adverse effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard
Immediate (Acute) Health Hazards
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Diisodecyl phthalate	
Ethylbenzene	1000 lbs.
Isophorone Diisocyanate	
Diisodecyl phthalate (mixed Is)	
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Calcium carbonate	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Xylene	10000 lbs
Titanium dioxide	10000 lbs
Calcium oxide	10000 lbs
Diisodecyl phthalate	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Stearic acid	10000 lbs
Aluminum oxide	10000 lbs
Dibutyl tin dilaurate	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Isophorone Diisocyanate
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
Calcium oxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Polyvinyl chloride
Calcium Carbonate (Limestone)
Xylene
Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 39 g/l
VOC Method 310 : 2.94 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date: 02/19/2019

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.